

メーカー	タイプ	形状 (据置形 or 可搬形)	馬力 [HP]	法定冷凍能力 [トン]	冷媒 封入量 [kg]	m1(1.8kg) 以下	m1~2× m1	2×m1~ m2(16kg)	m2以上	風量[m <sup>3</sup> /min]		角ダクト		ダクト					
										標準	最小	本数 [本]	断面積 [m <sup>2</sup> ]	風量 [m <sup>3</sup> /min]	風速 [m/s]	冷媒量 [kg]	冷媒漏洩時最大濃度 [kg/m <sup>3</sup> ]		
																	漏洩速度: 4分間全量	漏洩速度: 75kg/h	
<b>一体形除湿機</b>																			
A社	除湿機	据置形	2.0	0.57/0.69	1.60	○				23/26	23/26	1	0.06	23.00	6.10	1.60	0.017	0.054	
			5.0	1.30/1.55	2.90		○				53/54	48	1	0.19	48.00	4.26	2.90	0.015	0.026
B社	除湿機 床置型 定速	据置形	2.0	0.68/0.82	1.25	○					14.7		0.12	14.70	2.09	1.25	0.021	0.085	
			3.0	1.00/1.21	1.90		○				14.7		0.12	14.70	2.09	1.90	0.032	0.085	
			3.0	1.00/1.21	1.50		○				21		0.12	21.00	2.99	1.50	0.018	0.060	
			3.0	1.00/1.21	2.10		○				21		0.12	21.00	2.99	2.10	0.025	0.060	
			5.0	1.49/1.79	2.80		○				31		0.15	31.00	3.53	2.80	0.023	0.040	
			5.0	1.49/1.79	3.80			○			31		0.15	31.00	3.53	3.80	0.031	0.040	
			8.0	2.40/2.89	3.40			○			56		0.20	56.00	4.56	3.40	0.015	0.022	
			8.0	2.40/2.89	6.80				○		56		0.20	56.00	4.56	6.80	0.030	0.022	
			10.0	3.03/3.65	4.80				○		68		0.26	68.00	4.31	4.80	0.018	0.018	
			10.0	3.03/3.65	8.80					○	68		0.26	68.00	4.31	8.80	0.032	0.018	
	除湿機 床置型 インバータ	据置形	2.0	1.08	1.75	○					21		0.12	21.00	2.99	1.75	0.021	0.060	
			2.0	1.08	2.30		○				21		0.12	21.00	2.99	2.30	0.027	0.060	
			4.0	1.89	2.80		○				31		0.15	31.00	3.53	2.80	0.023	0.040	
			4.0	1.89	3.60		○				31		0.15	31.00	3.53	3.60	0.029	0.040	
			8.0	3.69	3.70			○			56		0.20	56.00	4.56	3.70	0.017	0.022	
			8.0	3.69	5.80				○		56		0.20	56.00	4.56	5.80	0.026	0.022	
			除湿機天埋型 (室内機)	据置形	3.0	1.17	3.90			○		21		0.23	21.00	1.54	3.90	0.046	0.060
			除湿機 小型床置	据置形	0.8	0.35	0.55	○				6		0.03	6.00	2.87	0.55	0.023	0.208
除湿機 小型天吊	据置形	1.2	0.35	0.55	○				6		0.03	6.00	2.87	0.55	0.023	0.208			
C社	一体形除湿機床置	可搬形	0.8	0.28	0.58	○					7			7	2.02	0.58	0.021	0.179	
			2.0	0.79	1.40	○					22			22	6.20	1.40	0.016	0.057	
			3.0	1.07	1.50	○					25			25	7.04	1.50	0.015	0.050	
		据置形	5.0	1.92	3.00		○				70			70	10.89	3.00	0.011	0.018	
			10.0	4.26	3.70			○			90			90	10.29	3.70	0.010	0.014	
			一体形除湿機天吊	据置形	0.8	0.28	0.66	○				8			8	4.26	0.66	0.021	0.156
D社	業務用除湿機	据置形	2.0	0.68/0.82	1.25	○					14.5		0.117	14.5	2.07	1.25	0.022	0.086	
			3.0	1.00/1.21	1.50	○					21		0.117	21	2.99	1.50	0.018	0.060	
			5.0	1.49/1.79	2.80		○				31		0.14625	31	3.53	2.80	0.023	0.040	
			8.0	2.40/2.89	3.40		○				58		0.20475	58	4.72	3.40	0.015	0.022	
			10	3.03/3.65	4.8			○			68		0.26325	68.00	4.31	4.8	0.018	0.018	
<b>一体形水冷</b>																			
A社	水冷エアコン	据置形	5.0	1.30/1.55	1.30	○					42.0	36.0	1	0.19	36.00	3.20	1.30	0.009	0.035
			8.0	2.08/2.48	2.10		○				72.0	65.0	1	0.23	65.00	4.61	2.10	0.008	0.019
			10.0	2.57/3.06	2.60		○				80.0	68.0	1	0.31	68.00	3.68	2.60	0.010	0.018
			15.0	4.16/4.96	4.60			○			135.0	115.0	1	0.32	115.00	6.08	4.60	0.010	0.011
			20.0	5.14/6.12	5.40			○			165.0	140.0	1	0.37	140.00	6.23	5.40	0.010	0.009
B社	水冷床置	据置形	5.0	1.41/1.70	1.80	○					31		0.16	31.00	3.31	1.80	0.015	0.040	
			7.5	2.26/2.71	3.80			○			46		0.22	46.00	3.48	3.80	0.021	0.027	
			10.0	2.82/3.40	4.20			○			61.5		0.28	61.50	3.62	4.20	0.017	0.020	
			15.0	4.41/5.31	4.0+2.3			○			91		0.36	91.00	4.20	4.00	0.011	0.014	
			20.0	5.64/6.80	4.3×2			○			125			125.00		4.30			
			25.0	6.34/7.66	4.9×2			○			154			154.00		4.90			
			30.0	8.46/10.20	4.3×3			○			183			183.00		4.30			
			40.0	11.46/13.82	10.00			○			250			250.00		10.00			
			50.0	14.02/16.90	13.00			○			310			310.00		13.00			
			60.0	17.30/20.84	15.00			○			380			380.00		15.00			
80.0	21.30/25.66	20.00				○		505			505.00		20.00						
C社	一体形水冷床置	据置形	5.0	1.55	1.30	○					35			35	3.11	1.30	0.009	0.036	
			8.0	2.48	2.10		○				65			65	4.61	2.10	0.008	0.019	
			10.0	3.06	2.60		○				70			70	3.79	2.60	0.009	0.018	
			15.0	4.96	4.60			○			115			115	6.08	4.60	0.010	0.011	
			20.0	6.12	5.40			○			140			140	6.41	5.40	0.010	0.009	
	一体形水冷天埋	据置形	1.0	0.39	0.64	○				9.5			9.5	1.07	0.64	0.017	0.132		
1.5	0.59	0.72	○					10.5			10.5	1.18	0.72	0.017	0.119				
3.0	1.07	1.41	○					30			30	7.51	1.41	0.012	0.042				
5.0	1.92	1.97		○				37			37	7.18	1.97	0.013	0.034				
D社	一体形水冷床置	据置形	5.0	1.41/1.70	1.80	○					31		0.138	31	3.74	1.80	0.015	0.040	
			8.0	2.26/2.71	3.80		○				46		0.191	46	4.01	3.80	0.021	0.027	
			10.0	2.82/3.40	4.20		○				61.5		0.246	61.5	4.17	4.20	0.017	0.020	
			16.0	4.41/5.31	4.0+2.3			○			91		0.282	91	5.38	4.00	0.011	0.014	
			20.0	5.64/6.80	4.3×2			○			126		0.277	126	7.58	4.30	0.009	0.010	
			25.0	6.34/7.66	4.9×2			○			154		0.286	154	8.97	4.90	0.008	0.008	
			28.0	8.46/10.20	4.3×3			○			182		0.311	182	9.75	4.30	0.006	0.007	
			<b>一体形スルーウォール</b>																
D社	一体形スルーウォール	据置形	0.9	0.279	1.30	○					6		0.06	6	1.72	1.30	0.054	0.208	
			1.4	0.488	1.30	○					8		0.06	8	2.30	1.30	0.041	0.156	
			0.9	0.263	0.80	○					7		0.07	7	1.60	0.80	0.029	0.179	
			1.3	0.406	0.80	○					7		0.07	7	1.60	0.80	0.029	0.179	
<b>一体形外置ダクト</b>																			
E社	一体形外置ダクト 標準	屋外据置形	8	3.42	11.5			○			63	52	1	0.12	52.00	7.22	11.5	0.055	0.024
			10	4.06	11.5			○			80	72	1	0.12	72.00	10.00	11.5	0.040	0.017
			16	4.0×2	5.5×2						140	100	1	0.2	100.00	8.33	5.5	0.014	0.013
			20	4.9×2	5.5×2						170	145	1	0.2	145.00	12.08	5.5	0.009	0.009
			25	4.0×3	5.5×3						210	170	1	0.26672	170.00	10.62	5.5	0.008	0.007
			30	4.9×3	5.5×3						255	200	1	0.26672	200.00	12.50	5.5	0.007	0.006
	一体形外置ダクト 中温用	屋外据置形	8	4	5.5			○			87	75	1	0.12	75.00	10.42	5.5	0.018	0.017
			16	4.0×2	5.5×2						170	145	1	0.2	145.00	12.08	5.5	0.009	0.009
			25	4.0×3	5.5×3						255	200	1	0.26672	200.00	12.50	5.5	0.007	0.006
	一体形外置ダクト 外調機	屋外据置形	8	4	5.5			○			28	22	1	0.12	22.00	3.06	5.5	0.063	0.057
			10	4.9	5.5			○			35	25	1	0.12	25.00	3.47	5.5	0.055	